


Airpel® -FFR Product Specifications



PFRN1-1



SFRN1-1

Compact System Specifications	System Components				
	High Precision Regulator (60 psi / 0.4 MPa)	High Precision Regulator (100 psi / 0.7 MPa)	Standard Regulator (120 psi / 0.85 MPa)	5 micron Filter	0.01 micron Coalescing Filter
System # PFRN1-1 (NPT ports)	PRN1-1	n/a	n/a	F5N1-1	FCN1-1
System # PFRG1-1 (G ports)	PRG1-1	n/a	n/a	F5G1-1	FCG1-1
System # PFRN1-2 (NPT ports)	n/a	PRN1-2	n/a	F5N1-1	FCN1-1
System # PFRG1-2 (G ports)	n/a	PRG1-2	n/a	F5G1-1	FCG1-1
System # SFRN1-1 (NPT ports)	n/a	n/a	SRN1-1	F5N1-1	FCN1-1
System # SFRG1-1 (G ports)	n/a	n/a	SRG1-1	F5G1-1	FCG1-1
Working Fluid	Clean Compressed Air	Clean Compressed Air	Compressed Air	Compressed Air	Compressed Air
Max. Working Pressure	150 psi / 1 MPa	150 psi / 1 MPa	150 psi / 1 MPa	150 psi / 1 MPa	15 to 150 psi / 0.1 to 1.0 MPa
Min. Working Pressure	Set Pressure + 15 psi / 0.1 MPa	Set Pressure + 15 psi / 0.1 MPa	n/a	n/a	n/a
Withstanding Pressure	220 psi / 1.5 MPa	220 psi / 1.5 MPa	220 psi / 1.5 MPa	220 psi / 1.5 MPa	220 psi / 1.5 MPa
Ambient Temp. Range/Fluid temp.	-5 to 60 °C (to be unfrozen)	-5 to 60 °C (to be unfrozen)	5 to 60 °C	5 to 60 °C	5 to 60 °C
Set Pressure Range	.7 psi to 60 psi / 0.005 to 0.4 MPa	.7 psi to 100 psi / 0.005 to 0.7 MPa	7 psi to 120 psi / 0.05 to 0.85 MPa	n/a	n/a
Sensitivity	.06 psi / 0.0004 MPa	.06 psi / 0.0004 MPa	n/a	n/a	n/a
Repeatability	.3 psi / 0.002 MPa	.3 psi / 0.002 MPa	n/a	n/a	n/a
Air Consumption	≤ 1.3 Std. L/min	≤ 1.3 Std. L/min	n/a	n/a	n/a
Filtration Rating	n/a	n/a	n/a	5 micron	0.01 micron
Relief Mechanism	Included	Included	Included	n/a	n/a
Drain Capacity	n/a	n/a	n/a	12 cm ³	3 cm ³
Port Size NPT or G	1/4	1/4	1/4	1/4	1/4
Product Weight	250 g	250 g	160 g	87 g	96 g
Standard Accessories	n/a	n/a	Pressure gauge, nut for panel mount	Bowl Guard	Bowl Guard
Maximum Flow Rate Primary Side Pressure 0.7 MPa / Pressure Drop 0.01 MPa	n/a	n/a	n/a	150 Std. L/min	150 Std. L/min
Secondary Side Oil Concentration	n/a	n/a	n/a	n/a	≤ 0.01 mg/m ³

Airpot Corporation, 35 Lois Street, Norwalk, CT 06851 USA
 800-848-7681 ■ 203-846-2021 ■ fax: 203-849-0539 ■ email: sales@airpot.com ■ www.airpot.com

Airpot®, Airpel®, and Anti-Stiction® are registered trademarks of Airpot Corporation

PUB# FFRS-04R